NSN 5925-01-278-7970

Circuit Breaker - Page 1 of 2

Instantaneous all locations



View Online at https://aerobasegroup.com/nsn/5925-01-278-7970

Body Style:
Multipole-single actuator type
Body Length:
10.000 inches
Body Width:
4.125 inches
Body Height:
4.062 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
8.375 inches
Center To Center Distance Between Terminals Parallel To Width:
1.375 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
9.125 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.375 inches
End Application:
Ships service switchboard model 803361 used onboard 270 ft b class coast guard vessels
Boss Height:
0.250 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
Features Provided:
Adjustable trip release
Maximum Continuous Load Current Rating Per Pole:
150.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
600.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
14000.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:

NSN 5925-01-278-7970

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:
+875.0/+1750.0 ac all locations
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
14.000 pounds
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:
A030a0