

View Online at <https://aerobasegroup.com/nsn/5925-01-279-5208>

Body Style:

Single pole type

Mounting Slot Width:

0.563 inches

Body Length:

4.250 inches

Body Width:

1.000 inches

Body Height:

2.625 inches

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Boss Height:

0.188 inches

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 slot and 1 terminal

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

277.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

14000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

9.000 at 200 pct single location and 70.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant and general purpose

Trip Release Ambient Temperature Rating:

40.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

1 compression and 1 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0