

View Online at <https://aerobasegroup.com/nsn/5925-01-281-3040>

Body Style:

Multipole-single actuator type

Overall Height:

9.826 inches

Mounting Slot Width:

1.125 inches

Body Length:

10.156 inches

Body Width:

4.937 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

8.750 inches

Center To Center Distance Between Terminals Parallel To Width:

3.250 inches

Unthreaded Mounting Hole Diameter:

0.875 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

8.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.625 inches

Boss Height:

0.187 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

2 slot and 4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

100.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1400.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

130.0 all locations

Reset Method:

Manual

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Special Features:

Current limiter fuse unit

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

3 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0