

View Online at <https://aerobasegroup.com/nsn/5925-01-281-3040>

**Body Style:**

Multipole-single actuator type

**Overall Height:**

9.826 inches

**Mounting Slot Width:**

1.125 inches

**Body Length:**

10.156 inches

**Body Width:**

4.937 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

8.750 inches

**Center To Center Distance Between Terminals Parallel To Width:**

3.250 inches

**Unthreaded Mounting Hole Diameter:**

0.875 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

8.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.625 inches

**Boss Height:**

0.187 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

2 slot and 4 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

100.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1400.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

130.0 all locations

**Reset Method:**

Manual

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Special Features:**

Current limiter fuse unit

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

3 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0