# NSN 5925-01-282-0020

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-282-0020

#### **Body Style:**

Rectangular dimensional envelope

#### **Overall Length:**

3.000 inches

# **Overall Height:**

1.500 inches

# **Overall Width:**

2.910 inches

#### **Case Material:**

Plastic

Fragility Factor:

Moderately rugged

#### **Pole Quantity:**

2

#### Arc Quenching Method:

Magnetic blowout

### Mounting Facility Type And Quantity:

4 terminal

# Storage Type:

General purpose warehouse

#### Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

# **Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

#### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

22000.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

#### Trip Release Method:

Magnetic all locations

#### **Trip Release Characteristic:**

Instantaneous all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

#### **Reset Method:**

Manual

#### Main Contact Tripping Mechanism Type:

Trip free

### Manual Actuator Type And Quantity:

1 toggle

### **Actuator Function:**

Trip-reset

# NSN 5925-01-282-0020

Circuit Breaker - Page 2 of 2



**Actuator Position Designation:** 

At pole two

Internal Trip Release Configuration:

Series trip all locations

Inclosure Protection Type For Which Designed:

Dustproof

Frequency In Hertz:

60.0 all locations

**Terminal Type And Quantity:** 

4 clip

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A030a0