NSN 5925-01-282-0510

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-282-0510 **Body Style:** Multipole-single actuator type **Body Length:** 6.000 inches **Body Width: 4.469 inches Body Height:** 3.156 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 5.125 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.500 inches **Unthreaded Mounting Hole Diameter:** 0.170 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 5.125 inches **Switch Contact Arrangement:** Single pole, double throw Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches **Fragility Factor:** Moderately rugged **Boss Height:** 0.125 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:**

480.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

30000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

NSN 5925-01-282-0510

Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Instantaneous all locations and time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Auxiliary Switch Function And Quantity:
3 alarm
Switch Location And Position Designation:
Internal at each pole
Trip Delay Time In Seconds Per Rated Continuous Current:
40.000 at 200 pct all locations and 125.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Switch Terminal Type:
Wire lead
Switch Current Rating And Type In Amps:
10.0 ac and 0.25 dc
Switch Voltage Rating And Type In Volts:
240.0 ac and 250.0 dc
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:

A030a0