NSN 5925-01-282-4591

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-282-4591

Body Style: Single pole type **Body Length:** Between 1.968 inches and 2.032 inches **Body Width:** Between 0.718 inches and 0.782 inches Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length: Between 1.528 inches and 1.592 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.628 inches and 1.692 inches **Fragility Factor:** Moderately rugged Mounting Surface To Terminal End Distance: Between 1.898 inches and 1.962 inches **Pole Quantity:** 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Features Provided:** High inrush protection Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 10.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic-hydraulic single location **Trip Release Characteristic:** Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 125.0 single location

NSN 5925-01-282-4591

Circuit Breaker - Page 2 of 2

Reset Method:	
Manual	
Main Contact Tripping Mechanism Type:	
Trip free	
Manual Actuator Type And Quantity:	
1 toggle	
Actuator Function:	
Trip-reset	
Actuator Position Designation:	
At pole one	
Internal Trip Release Configuration:	
Series trip single location	
Thread Size:	
0.138 inches	
Trip Delay Time In Seconds Per Rated Continuous Current:	
15.000 at 200 pct single location and 70.000 at 200 pct single location	
Inclosure Protection Type For Which Designed:	
Fungus resistant and moisture resistant	
Frequency In Hertz:	
50.0 single location or 60.0 single location	
Unpackaged Unit Weight:	
2.500 ounces	
Thread Series Designator:	
Unc	
Terminal Type And Quantity:	
2 quick disconnect, male	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A030a0	

