

View Online at <https://aerobasegroup.com/nsn/5925-01-285-1968>

Body Style:

Multipole-multiple actuator type

Body Length:

82.0 millimeters

Body Width:

54.0 millimeters

Body Height:

70.0 millimeters

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

13.5 millimeters

Unthreaded Mounting Hole Diameter:

4.0 millimeters

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Mounting Facility Type And Quantity:

2 unthreaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

3.2 amperes ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

320.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 push button

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two and between pole two and three

Inclsure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Frequency In Hertz:

50.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0