NSN 5925-01-285-2050

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-285-2050

•
Body Style:
Rectangular dimensional envelope
Overall Length:
22.000 inches
Overall Height:
7.438 inches
Overall Width:
9.000 inches
Fragility Factor:
Moderately rugged
Pole Quantity:
3
Arc Quenching Method:
Magnetic blowout
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Features Provided:
Adjustable trip release
Maximum Continuous Load Current Rating Per Pole:
500.0 amperes ac all locations and 500.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
500.0 ac all locations and 250.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
150.0 all locations
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:
+1900.0/+3500.0 ac all locations

50.0 degrees celsius all locations

Trip Release Ambient Tempurature Rating:

NSN 5925-01-285-2050

Circuit Breaker Tripper - Page 2 of 2



Freguency I	In Hertz:
-------------	-----------

400.0 all locations

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0