NSN 5925-01-286-2804



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-286-2804 **Body Style:** Rectangular dimensional envelope **Overall Length:** 3.400 inches **Overall Height:** 2.600 inches **Overall Width:** 3.900 inches **Case Material: Plastic Fragility Factor:** Moderately rugged **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 6 terminal Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 100.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

Actuator Function:

Trip-reset

NSN 5925-01-286-2804

Circuit Breaker - Page 2 of 2



Actuator Position Designation:
At pole two
Inclosure Protection Type For Which Designed:
Dustproof
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
3 clip and 3 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A030a0