# NSN 5925-01-286-8009

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-286-8009

### Body Style:

Multipole-multiple actuator type

#### **Body Length:**

2.490 inches

## Body Width:

2.250 inches

#### **Case Material:**

Plastic

#### Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

#### Center To Center Distance Between Terminals Parallel To Width:

#### 0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

#### 2.060 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

### 0.750 inches

**Fragility Factor:** 

Moderately rugged

#### **Boss Height:**

0.150 inches

#### Mounting Surface To Terminal End Distance:

2.810 inches

#### **Pole Quantity:**

3

# Arc Quenching Method:

Magnetic blowout

# Mounting Facility Type And Quantity:

6 threaded hole

# Storage Type:

General purpose warehouse

# Thready Qty Per Inch (tpi):

32

# Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac all locations

# Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

# Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

# **Circuit Protection Type:**

Overcurrent all locations

## Trip Release Method:

Magnetic all locations

# NSN 5925-01-286-8009

Circuit Breaker - Page 2 of 2



**Trip Release Characteristic:** Time delay all locations Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 125.0 all locations **Reset Method:** Manual Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 3 toggle Actuator Function: Trip-reset **Actuator Position Designation:** At each pole **External Actuator Linkage Arrangement:** One, two, and three linked Internal Trip Release Configuration: Series trip all locations **Thread Size:** 0.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: 0.200 at 200 pct all locations and 0.700 at 200 pct all locations **Inclosure Protection Type For Which Designed:** Dustproof **Frequency In Hertz:** 50.0 all locations or 60.0 all locations **Thread Series Designator:** Unc **Terminal Type And Quantity:** 6 threaded stud Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A030a0