

View Online at <https://aerobasegroup.com/nsn/5925-01-286-9299>

Body Style:

Single pole type

Bushing Length:

0.500 inches

Body Length:

1.375 inches

Body Width:

0.660 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.880 inches

Fragility Factor:

Moderately rugged

End Application:

Oscillator unit p/n m-478 onboard 110 ft wpb class cg vessels

Mounting Surface To Terminal End Distance:

1.815 inches

Pole Quantity:

1

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Cubic Measure:

4.000 cubic inches

Thready Qty Per Inch (tpi):

28

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac single location and 30.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location and 50.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location and 2000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

145.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Reset

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.437 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

6.000 at 200 pct single location and 30.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Shock resistant and vibration resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Unpackaged Unit Weight:

1.500 ounces

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0