

View Online at <https://aerobasegroup.com/nsn/5925-01-287-7552>

Body Style:

Rectangular dimensional envelope

Overall Length:

4.260 inches

Overall Height:

2.280 inches

Overall Width:

3.690 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.167 inches and 0.177 inches

Switch Contact Arrangement:

Single pole, double throw

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

35.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

216.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Auxiliary Trip Coil Voltage Type And Rating In Volts:

115.0 ac all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Electric

Main Contact Tripping Mechanism Type:

Trip free

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip w/auxiliary load terminal and remote trip feature all locations

Trip Release Duty Cycle:

Continuous all locations

Switch Location And Position Designation:

Internal at pole one

Reset Actuator Voltage Rating And Type In Volts:

115.0 ac

Inclosure Protection Type For Which Designed:

Dustproof

Trip Release Ambient Temperature Rating:

71.0 degrees celsius all locations

Switch Terminal Type:

Pin

Switch Current Rating And Type In Amps:

3.0 ac

Switch Voltage Rating And Type In Volts:

115.0 ac

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0