## NSN 5925-01-287-7552

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-287-7552

Body Style:
Rectangular dimensional envelope
Overall Length:
4.260 inches
Overall Height:
2.280 inches
Overall Width:
3.690 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
Between 0.167 inches and 0.177 inches
Switch Contact Arrangement:
Single pole, double throw
Fragility Factor:
Moderately rugged
Pole Quantity:
3
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
4 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
35.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
115.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
216.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal all locations
Auxiliary Trip Coil Voltage Type And Rating In Volts:
115.0 ac all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
150.0 all locations

Electric

**Reset Method:** 

## NSN 5925-01-287-7552

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Auxiliary Switch Function And Quantity:
1 alarm
Internal Trip Release Configuration:
Series trip w/auxiliary load terminal and remote trip feature all locations
Trip Release Duty Cycle:
Continuous all locations
Switch Location And Position Designation:
Internal at pole one
Reset Actuator Voltage Rating And Type In Volts:
115.0 ac
Inclosure Protection Type For Which Designed:
Dustproof
Trip Release Ambient Tempurature Rating:
71.0 degrees celsius all locations
Switch Terminal Type:
Pin
Switch Current Rating And Type In Amps:
3.0 ac
Switch Voltage Rating And Type In Volts:
115.0 ac
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0