## NSN 5925-01-290-4805

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-290-4805

| Overall Length:   |
|---|
| 2.875 inches  |
| Overall Height:   |
| 1.000 inches  |
| Overall Width:  |
| 2.375 inches  |
| Case Material:  |
| Plastic   |
| Fragility Factor:   |
| Moderately rugged   |
| Pole Quantity:  |
| 1   |
| Mounting Facility Type And Quantity:                                    |
| 2 clip  |
| Storage Type:   |
| General purpose warehouse   |
| Features Provided:  |
| Ground fault protection   |
| Maximum Continuous Load Current Rating Per Pole:                        |
| 20.0 amperes ac single location   |
| Operating Voltage Type And Rating Per Pole In Volts:                    |
| 240.0 ac single location  |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 10000.0 ac single location  |
| Circuit Protection Type:  |
| Overcurrent single location   |
| Trip Release Method:  |
| Thermal-magnetic single location  |
| Trip Release Characteristic:  |
| Instantaneous single location   |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:  |
| 125.0 single location   |
| Reset Method:   |
| Manual  |
| Main Contact Tripping Mechanism Type:                                   |
| Trip free   |
| Manual Actuator Type And Quantity:                                      |
| 1 toggle  |
| Actuator Function:  |
| Trip-reset  |
| Actuator Position Designation:  |

At pole one

## NSN 5925-01-290-4805

Circuit Breaker - Page 2 of 2



| inclosure Protection Type | e For Which Designed |
|---------------------------|----------------------|
| Fungus proof and moisture | resistant            |

**Trip Release Ambient Tempurature Rating:** 

40.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

**Terminal Type And Quantity:** 

2 compression

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0