

View Online at <https://aerobasegroup.com/nsn/5925-01-292-2047>

Body Style:

Rectangular dimensional envelope

Overall Length:

2.375 inches

Overall Height:

1.000 inches

Overall Width:

2.312 inches

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 clip and 1 terminal

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

22000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Inclosure Protection Type For Which Designed:

Fungus proof

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

1 compression and 1 clip

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0