## NSN 5925-01-293-2306



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-293-2306 **Body Style:** Rectangular dimensional envelope **Overall Length:** 100.0 millimeters **Overall Height:** 54.0 millimeters **Overall Width:** 92.5 millimeters **Case Material: Plastic Fragility Factor:** Moderately rugged **Pole Quantity: Mounting Facility Type And Quantity:** 2 terminal Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 10.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 300.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 

1 rotary

**Actuator Function:** 

Trip-reset

## NSN 5925-01-293-2306

Circuit Breaker - Page 2 of 2



Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Frequency In Hertz:
50.0 all locations or 60.0 all locations
Unpackaged Unit Weight:
0.520 pounds
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0