

View Online at <https://aerobasegroup.com/nsn/5925-01-293-9163>

Body Style:

Rectangular dimensional envelope

Overall Length:

6.500 inches

Overall Height:

4.125 inches

Overall Width:

4.875 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.201 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

100.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

15000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Auxiliary Switch Function And Quantity:

1 alarm

Adjustable Trip Setting Current Range Per Pole In Amps:

+500.0/+1400.0 ac all locations

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Special Features:

Item includes a 120 volt, 60 hertz shunt trip device

Frequency In Hertz:

400.0 all locations

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0