

View Online at <https://aerobasegroup.com/nsn/5925-01-293-9163>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

6.500 inches

**Overall Height:**

4.125 inches

**Overall Width:**

4.875 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.201 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Features Provided:**

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:**

100.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

15000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Auxiliary Switch Function And Quantity:**

1 alarm

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+500.0/+1400.0 ac all locations

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Special Features:**

Item includes a 120 volt, 60 hertz shunt trip device

**Frequency In Hertz:**

400.0 all locations

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0