NSN 5925-01-294-4577

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-294-4577

## **Body Style:**

Rectangular dimensional envelope

### **Overall Length:**

9.578 inches

# **Overall Height:**

3.000 inches

### **Overall Width:**

4.000 inches

#### **Case Material:**

Plastic

#### **Unthreaded Mounting Hole Diameter:**

0.250 inches

#### Fragility Factor:

Moderately rugged

#### **Pole Quantity:**

3

#### Arc Quenching Method:

Magnetic blowout

## Mounting Facility Type And Quantity:

4 unthreaded hole

## Storage Type:

General purpose warehouse

## **Special Handling Feature:**

Magnetic

## Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

## **Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations

#### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

18000.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

#### **Trip Release Method:**

Thermal-magnetic all locations

#### **Trip Release Characteristic:**

Instantaneous all locations

## Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

## **Reset Method:**

Manual

### Main Contact Tripping Mechanism Type:

Trip free

# NSN 5925-01-294-4577

Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity: 1 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole two Inclosure Protection Type For Which Designed: Dustproof **Trip Release Ambient Tempurature Rating:** 50.0 degrees celsius all locations **Frequency In Hertz:** 60.0 all locations **Terminal Type And Quantity:** 6 compression Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A030a0