## NSN 5925-01-294-4579

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-294-4579

**Body Style:** Rectangular dimensional envelope **Overall Length:** 9.578 inches **Overall Height:** 3.000 inches **Overall Width:** 4.000 inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.250 inches **Fragility Factor:** Moderately rugged **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 4 unthreaded hole **Storage Type:** General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 40.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 18000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 

125.0 all locations

**Reset Method:** 

Manual

**Main Contact Tripping Mechanism Type:** 

Trip free

## NSN 5925-01-294-4579

Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
nclosure Protection Type For Which Designed:
Dustproof
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
4030a0