

View Online at <https://aerobasegroup.com/nsn/5925-01-294-5706>

Body Style:

Rectangular dimensional envelope

Overall Length:

22.562 inches

Overall Height:

3.875 inches

Overall Width:

8.250 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.250 inches

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

600.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

480.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

100000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Adjustable Trip Setting Current Range Per Pole In Amps:

+3000.0/+6000.0 ac all locations

Inclosure Protection Type For Which Designed:

Dustproof

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Special Features:

Includes shunt trip device rated at 120 vac and 48 vdc

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0