## NSN 5925-01-296-1002

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-296-1002

| Body Style:  |
|--|
| Multipole-single actuator type   |
| Body Length:   |
| 10.000 inches  |
| Body Width:  |
| 4.125 inches   |
| Body Height:   |
| 4.062 inches   |
| Case Material:   |
| Plastic  |
| Center To Center Distance Between Terminals Parallel To Length:              |
| 9.000 inches   |
| Center To Center Distance Between Terminals Parallel To Width:               |
| 1.375 inches   |
| Unthreaded Mounting Hole Diameter:   |
| 0.250 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 7.250 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:  |
| 1.375 inches   |
| Fragility Factor:  |
| Moderately rugged  |
| Boss Height:   |
| 0.250 inches   |
| Pole Quantity:   |
| 3  |
| Arc Quenching Method:  |
| Magnetic blowout   |
| Mounting Facility Type And Quantity:   |
| 4 unthreaded hole  |
| Storage Type:  |
| General purpose warehouse  |
| Special Handling Feature:  |
| Magnetic   |
| Features Provided:   |
| Adjustable trip release  |
| Maximum Continuous Load Current Rating Per Pole:                             |
| 30.0 amperes ac all locations and 30.0 amperes dc all locations              |
| Operating Voltage Type And Rating Per Pole In Volts:                         |
| 600.0 ac all locations and 250.0 dc all locations                            |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:      |

25000.0 ac all locations and 10000.0 dc all locations

## NSN 5925-01-296-1002

Circuit Breaker - Page 2 of 2



| Circuit Protection Type:   |
|--|
| Overcurrent all locations  |
| Trip Release Method:   |
| Magnetic all locations   |
| Trip Release Characteristic:   |
| Instantaneous all locations  |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 125.0 all locations  |
| Reset Method:  |
| Manual   |
| Main Contact Tripping Mechanism Type:                                  |
| Trip free  |
| Manual Actuator Type And Quantity:                                     |
| 1 toggle   |
| Actuator Function:   |
| Trip-reset   |
| Actuator Position Designation:   |
| At pole two  |
| Adjustable Trip Setting Current Range Per Pole In Amps:                |
| +90.0/+300.0 ac all locations and +90.0/+300.0 dc all locations        |
| Internal Trip Release Configuration:                                   |
| Series trip all locations  |
| Inclosure Protection Type For Which Designed:                          |
| Dustproof  |
| Frequency In Hertz:  |
| 60.0 all locations   |
| Terminal Type And Quantity:  |
| 6 compression  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A030a0   |
|  |