

View Online at <https://aerobasegroup.com/nsn/5925-01-296-8304>

Body Style:

Multipole-multiple actuator type

Body Length:

Between 2.480 inches and 2.500 inches

Body Width:

2.250 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.050 inches and 2.070 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.150 inches

Mounting Surface To Terminal End Distance:

2.475 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

6 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One, two, and three linked

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

3.0 millimeters

Thread Pitch In Millimeters:

0.50

Trip Delay Time In Seconds Per Rated Continuous Current:

0.180 at 200 pct all locations and 1.800 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Moisture resistant and salt spray proof and shock resistant and vibration resistant

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Unpackaged Unit Weight:

11.100 ounces

Thread Series Designator:

Iso s

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0