

View Online at <https://aerobasegroup.com/nsn/5925-01-296-8706>

**Body Style:**

Single pole type

**Overall Length:**

2.000 inches

**Body Width:**

1.250 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

0.906 inches

**Unthreaded Mounting Hole Diameter:**

0.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.574 inches

**Fragility Factor:**

Moderately rugged

**Mounting Surface To Terminal End Distance:**

1.234 inches

**Pole Quantity:**

1

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

5.0 amperes ac all locations and 5.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

110.0 ac all locations and 30.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

600.0 ac all locations and 600.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Automatic

**Internal Trip Release Configuration:**

Series trip all locations

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

2 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0