NSN 5925-01-296-8706

Circuit Breaker - Page 1 of 2

Body Style:
Single pole type
Overall Length:
2.000 inches



View Online at https://aerobasegroup.com/nsn/5925-01-296-8706

Body Width:
1.250 inches
Case Material:
Metal
Center To Center Distance Between Terminals Parallel To Length:
0.906 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.574 inches
Fragility Factor:
Moderately rugged
Mounting Surface To Terminal End Distance:
1.234 inches
Pole Quantity:
1
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
2 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
5.0 amperes ac all locations and 5.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
110.0 ac all locations and 30.0 dc all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
600.0 ac all locations and 600.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Automatic

NSN 5925-01-296-8706

Circuit Breaker - Page 2 of 2



Internal Trip Release Configuration:
Series trip all locations
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
2 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A030a0