NSN 5925-01-297-5906



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-297-5906 **Body Style:** Rectangular dimensional envelope **Overall Length:** 3.000 inches **Overall Height:** 2.250 inches **Overall Width:** 2.310 inches **Case Material: Plastic Fragility Factor:** Moderately rugged **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 2 terminal Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 70.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 22000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

Actuator Function:

Trip-reset

NSN 5925-01-297-5906

Circuit Breaker - Page 2 of 2



Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Inclosure Protection Type For Which Designed:
Dustproof
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
2 clip
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0