

View Online at <https://aerobasegroup.com/nsn/5925-01-299-1942>

Body Style:

Rectangular dimensional envelope

Overall Length:

22.563 inches

Overall Height:

3.875 inches

Overall Width:

8.250 inches

Case Material:

Plastic

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 threaded hole

Features Provided:

Adjustable trip release and current limiter

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

500.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

480.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

100000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Adjustable Trip Setting Current Range Per Pole In Amps:

+2500.0/+5000.0 ac all locations

Thread Size:

0.250 inches

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Special Features:

Fusematic circuit breaker; load lugs included

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0