## NSN 5925-01-299-3568



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-299-3568 **Body Style:** Multipole-multiple actuator type Case Material: Plastic **Switch Contact Arrangement:** Single pole, double throw **Pole Quantity:** 2 **Maximum Continuous Load Current Rating Per Pole:** 2.0 amperes ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 20.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal all locations **Trip Release Characteristic:** Instantaneous all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 2 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At each pole

**External Actuator Linkage Arrangement:** 

One and two linked

**Auxiliary Switch Function And Quantity:** 

**Internal Trip Release Configuration:** 

Series trip all locations

**Trip Release Ambient Tempurature Rating:** 

45.0 degrees celsius all locations

**Switch Current Rating And Type In Amps:** 

6.0 ac and 3.0 dc

**Switch Voltage Rating And Type In Volts:** 

220.0 ac and 110.0 dc

**Terminal Type And Quantity:** 

4 screw

## NSN 5925-01-299-3568

Circuit Breaker - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0