

View Online at <https://aerobasegroup.com/nsn/5925-01-299-3568>

Body Style:

Multipole-multiple actuator type

Case Material:

Plastic

Switch Contact Arrangement:

Single pole, double throw

Pole Quantity:

2

Maximum Continuous Load Current Rating Per Pole:

2.0 amperes ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

20.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Instantaneous all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One and two linked

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip all locations

Trip Release Ambient Temperature Rating:

45.0 degrees celsius all locations

Switch Current Rating And Type In Amps:

6.0 ac and 3.0 dc

Switch Voltage Rating And Type In Volts:

220.0 ac and 110.0 dc

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0