

View Online at <https://aerobasegroup.com/nsn/5925-01-299-3570>

Body Style:

Multipole-single actuator type

Body Length:

622.0 millimeters

Body Width:

454.0 millimeters

Body Height:

447.5 millimeters

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

58.0 millimeters

Boss Height:

40.0 millimeters

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 terminal

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

1.9 milliamperes ac all locations and 1.9 milliamperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations and 220.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

60000.0 ac all locations and 60000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Electric

Main Contact Tripping Mechanism Type:

Trip free

Adjustable Trip Setting Current Range Per Pole In Amps:

+3000.0/+6000.0 ac all locations and +3000.0/+6000.0 dc all locations

Internal Trip Release Configuration:

Series trip all locations

Reset Actuator Voltage Rating And Type In Volts:

240.0 ac and 220.0 dc

Inclosure Protection Type For Which Designed:

Corrosion resistant and dustproof

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0