

View Online at <https://aerobasegroup.com/nsn/5925-01-299-3572>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

82.5 millimeters

**Overall Height:**

54.0 millimeters

**Overall Width:**

82.0 millimeters

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

4.5 millimeters

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Storage Type:**

General purpose warehouse

**Features Provided:**

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:**

12.5 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

380.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

150.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

2 push button

**Actuator Function:**

Trip w/separate reset

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+8.0/+12.5 ac all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

90.000 at 200 pct all locations

**Inclsoure Protection Type For Which Designed:**

General purpose

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Frequency In Hertz:**

50.0 all locations

**Unpackaged Unit Weight:**

0.29 kilograms

**Terminal Type And Quantity:**

6 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0