

View Online at <https://aerobasegroup.com/nsn/5925-01-299-3572>

Body Style:

Rectangular dimensional envelope

Overall Length:

82.5 millimeters

Overall Height:

54.0 millimeters

Overall Width:

82.0 millimeters

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

4.5 millimeters

Pole Quantity:

3

Mounting Facility Type And Quantity:

2 unthreaded hole

Storage Type:

General purpose warehouse

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

12.5 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

380.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

150.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 push button

Actuator Function:

Trip w/separate reset

Adjustable Trip Setting Current Range Per Pole In Amps:

+8.0/+12.5 ac all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

90.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Frequency In Hertz:

50.0 all locations

Unpackaged Unit Weight:

0.29 kilograms

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0