NSN 5925-01-300-5835

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-300-5835

view Online at https://aerobasegroup.com/nsn/5925-01-300-5635
Body Style:
Rectangular dimensional envelope
Overall Length:
21.875 inches
Overall Height:
5.875 inches
Overall Width:
8.250 inches
Unthreaded Mounting Hole Diameter:
0.388 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
Features Provided:
Adjustable trip release and interchangeable trip release
Maximum Continuous Load Current Rating Per Pole:
400.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
600.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
Between pole one and two
Adjustable Trip Setting Current Range Per Pole In Amps:
+1200.0/+3500.0 ac all locations
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:

6 compression

NSN 5925-01-300-5835

Circuit Breaker Tripper - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0