

View Online at <https://aerobasegroup.com/nsn/5925-01-302-4061>

Body Style:

Multipole-multiple actuator type

Body Length:

2.000 inches

Body Width:

2.265 inches

Case Material:

Plastic

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.660 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Boss Height:

0.130 inches

Mounting Surface To Terminal End Distance:

2.032 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 threaded hole

Maximum Continuous Load Current Rating Per Pole:

3.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Manual Actuator Type And Quantity:

3 toggle

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

60.000 at 150 pct all locations

Inclosure Protection Type For Which Designed:

Moisture resistant

Frequency In Hertz:

400.0 all locations

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0