## NSN 5925-01-302-4266



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-302-4266 **Overall Length:** 3.281 inches **Overall Height:** 1.000 inches **Overall Width:** 2.375 inches **Case Material:** Plastic **Unthreaded Mounting Hole Diameter:** 0.380 inches **Fragility Factor:** Moderately rugged **Pole Quantity: Mounting Facility Type And Quantity:** 2 unthreaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 22000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal-magnetic single location **Trip Release Characteristic:** Instantaneous single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

**Actuator Function:** 

Trip-reset

## NSN 5925-01-302-4266

Circuit Breaker - Page 2 of 2



Actuator Position Designation:
At pole one
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius single location
Frequency In Hertz:
60.0 single location
Terminal Type And Quantity:
2 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A030a0