

View Online at <https://aerobasegroup.com/nsn/5925-01-303-3340>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

483.0 millimeters

**Overall Height:**

337.0 millimeters

**Overall Width:**

338.0 millimeters

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

10.5 millimeters

**Switch Contact Arrangement:**

Single pole, double throw

**Fragility Factor:**

Moderately rugged

**Pole Quantity:**

3

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Storage Type:**

General purpose warehouse

**Features Provided:**

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:**

420.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

40000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

2 push button

**Actuator Function:**

Trip w/separate reset

**Auxiliary Switch Function And Quantity:**

2 control

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+1200.0/+2500.0 ac all locations

**Internal Trip Release Configuration:**

Series trip all locations

**Inclosure Protection Type For Which Designed:**

General purpose

**Trip Release Ambient Temperature Rating:**

35.0 degrees celsius all locations

**Special Features:**

1 undervoltage release device and 1 shunt release device included

**Frequency In Hertz:**

60.0 all locations

**Unpackaged Unit Weight:**

32.2 kilograms

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0