NSN 5925-01-303-4069

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-303-4069

Body Style:

Multipole-multiple actuator type

Body Length:

2.510 inches

Body Width:

2.245 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.810 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

End Application:

An/sqq-89-v-unit 123

Boss Height:

0.140 inches

Mounting Surface To Terminal End Distance:

2.553 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 threaded stud

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

NSN 5925-01-303-4069

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 3 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At each pole **External Actuator Linkage Arrangement:** One, two, and three linked Internal Trip Release Configuration: Series trip all locations Thread Size: 0.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: 3.000 at 200 pct all locations **Inclosure Protection Type For Which Designed:** Fungus resistant **Frequency In Hertz:** 60.0 all locations **Thread Series Designator:** Unc **Terminal Type And Quantity:** 6 threaded stud Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A030a0