

View Online at <https://aerobasegroup.com/nsn/5925-01-303-4724>

Body Style:

Rectangular dimensional envelope

Overall Length:

529.0 millimeters

Overall Height:

339.0 millimeters

Overall Width:

358.0 millimeters

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

12.5 millimeters

Switch Contact Arrangement:

Single pole, double throw

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

420.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

25000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 push button

Actuator Function:

Trip w/separate reset

Auxiliary Switch Function And Quantity:

2 control

Adjustable Trip Setting Current Range Per Pole In Amps:

+1200.0/+2500.0 ac all locations

Internal Trip Release Configuration:

Series trip all locations

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

35.0 degrees celsius all locations

Special Features:

1 undervoltage release device and 1 shunt release device included; with motorized stored energy operating mechanism

Frequency In Hertz:

60.0 all locations

Unpackaged Unit Weight:

41.1 kilograms

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0