## NSN 5925-01-303-4724

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-303-4724

Body Style:
Rectangular dimensional envelope
Overall Length:
529.0 millimeters
Overall Height:
339.0 millimeters
Overall Width:
358.0 millimeters
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
12.5 millimeters
Switch Contact Arrangement:
Single pole, double throw
Fragility Factor:
Moderately rugged
Pole Quantity:
3
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 unthreaded hole
Storage Type:
General purpose warehouse
Features Provided:
Adjustable trip release
Maximum Continuous Load Current Rating Per Pole:
420.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
25000.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:

Manual

## **NSN 5925-01-303-4724** Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
2 push button
Actuator Function:
Trip w/separate reset
Auxiliary Switch Function And Quantity:
2 control
Adjustable Trip Setting Current Range Per Pole In Amps:
+1200.0/+2500.0 ac all locations
Internal Trip Release Configuration:
Series trip all locations
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
35.0 degrees celsius all locations
Special Features:
1 undervoltage release device and 1 shunt release device included; with motorized stored energy operating mechanism
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
41.1 kilograms
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A030a0