

View Online at <https://aerobasegroup.com/nsn/5925-01-304-0364>

Body Style:

Multipole-multiple actuator type

Bushing Length:

0.625 inches

Body Length:

2.000 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.530 inches

Mounting Surface To Terminal End Distance:

2.232 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 threaded stud

Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2100.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Ultimate Trip Time Per Pole In Seconds:

70.000 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Auxiliary Switch Function And Quantity:

1 control

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.187 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

5.000 at 150 pct all locations and 70.000 at 150 pct all locations

Frequency In Hertz:

400.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0