NSN 5925-01-304-0370

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-304-0370

Body Style:
Single pole type
Bushing Length:
0.380 inches
Body Length:
1.500 inches
Body Width:
0.625 inches
Case Material:
Matal

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.875 inches

Switch Contact Arrangement:

Single pole, double throw

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.605 inches

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

17.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

32.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.375 inches

Switch Location And Position Designation:

Internal at pole one

Trip Delay Time In Seconds Per Rated Continuous Current: 0.850 at 200 pct single location and 4.000 at 200 pct single location **Inclosure Protection Type For Which Designed:** Hermetically sealed Switch Terminal Type: Tab, solder lug Switch Current Rating And Type In Amps: 0.5 ac and 0.5 dc Switch Voltage Rating And Type In Volts: 120.0 ac and 50.0 dc **Thread Series Designator:** Unef **Terminal Type And Quantity:** 2 tab w/screw Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig:

A030a0