NSN 5925-01-304-0507

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-304-0507

Body Style: Single pole type **Body Length:** Between 2.475 inches and 2.505 inches **Body Width:** Between 0.735 inches and 0.765 inches Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length: Between 1.925 inches and 1.955 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.045 inches and 2.075 inches **Fragility Factor:** Moderately rugged **Boss Height:** Between 0.125 inches and 0.155 inches **Mounting Surface To Terminal End Distance:** Between 1.971 inches and 2.031 inches **Pole Quantity:** 1 Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 50.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 125.0 single location **Reset Method:** Manual

NSN 5925-01-304-0507

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 1 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole one Internal Trip Release Configuration: Series trip single location Thread Size: 0.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: 0.180 at 200 pct single location and 1.800 at 200 pct single location **Inclosure Protection Type For Which Designed:** General purpose **Frequency In Hertz:** 50.0 single location or 60.0 single location **Thread Series Designator:** Unc **Terminal Type And Quantity:** 2 screw Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A030a0