NSN 5925-01-304-3248

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-304-3248

Thread Pitch Diameters:
+0.3503/+0.3537 inches
Body Style:
Multipole-single actuator type
Bushing Length:
0.380 inches
Body Length:
1.500 inches
Body Width:
1.875 inches
Case Material:
Metal
Center To Center Distance Between Terminals Parallel To Length:
Between 0.844 inches and 0.906 inches
Center To Center Distance Between Terminals Parallel To Width:
Between 0.594 inches and 0.656 inches
Fragility Factor:
Moderately rugged
Mounting Surface To Terminal End Distance:
1.780 inches
Pole Quantity:
Pole Quantity: 3
3
3 Arc Quenching Method:
3 Arc Quenching Method: Magnetic blowout
Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity:
Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 1 threaded bushing w/panel seal
Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 1 threaded bushing w/panel seal Storage Type:
Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 1 threaded bushing w/panel seal Storage Type: General purpose warehouse
Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 1 threaded bushing w/panel seal Storage Type: General purpose warehouse Special Handling Feature:
Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 1 threaded bushing w/panel seal Storage Type: General purpose warehouse Special Handling Feature: Magnetic
Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 1 threaded bushing w/panel seal Storage Type: General purpose warehouse Special Handling Feature: Magnetic Thready Qty Per Inch (tpi):
Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 1 threaded bushing w/panel seal Storage Type: General purpose warehouse Special Handling Feature: Magnetic Thready Qty Per Inch (tpi): 32
Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 1 threaded bushing w/panel seal Storage Type: General purpose warehouse Special Handling Feature: Magnetic Thready Qty Per Inch (tpi): 32 Circuit Protection Type:
Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 1 threaded bushing w/panel seal Storage Type: General purpose warehouse Special Handling Feature: Magnetic Thready Qty Per Inch (tpi): 32 Circuit Protection Type: Overcurrent all locations
Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 1 threaded bushing w/panel seal Storage Type: General purpose warehouse Special Handling Feature: Magnetic Thready Qty Per Inch (tpi): 32 Circuit Protection Type: Overcurrent all locations Trip Release Method:
Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 1 threaded bushing w/panel seal Storage Type: General purpose warehouse Special Handling Feature: Magnetic Thready Qty Per Inch (tpi): 32 Circuit Protection Type: Overcurrent all locations Trip Release Method: Magnetic all locations
Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 1 threaded bushing w/panel seal Storage Type: General purpose warehouse Special Handling Feature: Magnetic Thready Qty Per Inch (tpi): 32 Circuit Protection Type: Overcurrent all locations Trip Release Method: Magnetic all locations Reset Method:
Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 1 threaded bushing w/panel seal Storage Type: General purpose warehouse Special Handling Feature: Magnetic Thready Qty Per Inch (tpi): 32 Circuit Protection Type: Overcurrent all locations Trip Release Method: Magnetic all locations Reset Method: Manual

1 toggle

NSN 5925-01-304-3248

Circuit Breaker - Page 2 of 2

A030a0

