

View Online at <https://aerobasegroup.com/nsn/5925-01-304-6755>

Thread Pitch Diameters:

+0.3503/+0.3537 inches

Body Style:

Multipole-single actuator type

Bushing Length:

0.380 inches

Body Length:

1.562 inches

Body Width:

1.937 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.875 inches

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

Nonturn Device Location:

At 3 o'clock and at 9 o'clock

Nonturn Device Radius:

0.625 inches

Nonturn Device Length:

0.130 inches

Nonturn Device Diameter:

0.140 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.780 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

1.150 at 200 pct all locations and 7.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Hermetically sealed and shock resistant and vibration resistant

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Unpackaged Unit Weight:

5.400 ounces

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0