## NSN 5925-01-306-6994

Circuit Breaker - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5925-01-306-6994
Body Style:
Multipole-single actuator type
Bushing Length:
Between 0.332 inches and 0.380 inches
Body Length:
1.562 inches
Body Width:
1.281 inches
Case Material:
Metal
Center To Center Distance Between Terminals Parallel To Length:
0.906 inches
Center To Center Distance Between Terminals Parallel To Width:
0.625 inches
End Application:
Aegis icss unique items
Mounting Surface To Terminal End Distance:
1.828 inches
Pole Quantity:
2
Mounting Facility Type And Quantity:
1 threaded bushing w/panel seal
Features Provided:
High inrush protection
Maximum Continuous Load Current Rating Per Pole:
1.0 amperes ac all locations and 1.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac all locations and 50.0 dc all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
300.0 ac all locations and 500.0 dc all locations
Circuit Protection Type:
Overvoltage all locations
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:

Trip free

## **NSN 5925-01-306-6994** Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
Between pole one and two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.200 at 135 pct all locations and 7.000 at 135 pct all locations
Frequency In Hertz:
60.0 all locations or 400.0 all locations
Thread Series Designator:
Unef
Terminal Type And Quantity:
4 wire hook
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0