NSN 5925-01-307-2008

Circuit Breaker - Page 1 of 2

Frequency In Hertz: 60.0 all locations



View Online at https://aerobasegroup.com/nsn/5925-01-307-2008 **Body Style:** Multipole-multiple actuator type **Body Length:** 5.800 inches **Body Width:** 2.072 inches **Body Height:** 2.610 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 1.026 inches **Boss Height:** 0.700 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole **Maximum Continuous Load Current Rating Per Pole:** 100.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 100.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 200.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Internal Trip Release Configuration:** Series trip all locations **Thread Size:** 4.060 millimeters

NSN 5925-01-307-2008

Circuit Breaker - Page 2 of 2



Thread Series Designator:
Unc
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A030a0