## NSN 5925-01-307-7076

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-307-7076

**Body Style:** Single pole type **Body Length:** Between 1.985 inches and 2.015 inches **Body Width:** Between 0.735 inches and 0.765 inches Case Material: Plastic **Center To Center Distance Between Terminals Parallel To Length:** Between 1.645 inches and 1.675 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.645 inches and 1.675 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 2.000 inches **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 2 threaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): **Maximum Continuous Load Current Rating Per Pole:** 7.5 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic-hydraulic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 

125.0 single location

## **NSN 5925-01-307-7076** Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
2.000 at 200 pct single location and 20.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Moisture resistant and salt water resistant and shock resistant and vibration resistant
Frequency In Hertz:
50.0 single location or 60.0 single location
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0