

View Online at <https://aerobasegroup.com/nsn/5925-01-308-0668>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

Between 0.332 inches and 0.380 inches

**Body Length:**

1.560 inches

**Body Width:**

1.250 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

0.880 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.630 inches

**Nonturn Device Location:**

At 9 oclock and at 3 oclock

**Nonturn Device Radius:**

0.625 inches

**Nonturn Device Length:**

0.130 inches

**Nonturn Device Diameter:**

0.250 inches

**Fragility Factor:**

Moderately rugged

**Mounting Surface To Terminal End Distance:**

1.750 inches

**Pole Quantity:**

2

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

5.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

115.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

Between pole one and two

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.375 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

1.200 at 200 pct all locations and 6.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Hermetically sealed

**Frequency In Hertz:**

60.0 all locations

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

4 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0