# NSN 5925-01-308-5406

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-308-5406

#### Body Style:

Rectangular dimensional envelope

#### **Overall Length:**

3.281 inches

# **Overall Height:**

1.000 inches

## **Overall Width:**

2.375 inches

#### **Case Material:**

Plastic

## **Unthreaded Mounting Hole Diameter:**

0.196 inches

#### Fragility Factor:

Moderately rugged

#### **Pole Quantity:**

1

## Arc Quenching Method:

Magnetic blowout

# Mounting Facility Type And Quantity:

2 unthreaded hole

#### Storage Type:

General purpose warehouse

#### Maximum Continuous Load Current Rating Per Pole:

35.0 amperes ac single location

#### **Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac single location

#### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

22000.0 ac single location

#### **Circuit Protection Type:**

Overcurrent single location

#### **Trip Release Method:**

Thermal-magnetic single location

#### **Trip Release Characteristic:**

Instantaneous single location

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

## **Reset Method:**

Manual

#### Main Contact Tripping Mechanism Type:

Trip free

#### Manual Actuator Type And Quantity:

1 toggle

# NSN 5925-01-308-5406

Circuit Breaker - Page 2 of 2



**Actuator Function:** Trip-reset **Actuator Position Designation:** At pole one Inclosure Protection Type For Which Designed: General purpose Trip Release Ambient Tempurature Rating: 25.0 degrees celsius single location Frequency In Hertz: 60.0 single location Terminal Type And Quantity: 2 compression Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A030a0